

CENTURION P8 BELT DRIVE TRIPLEX 3500 PSI 5.5GPM PRESSURE WASHER PUMP – 85.129.190B



With a belt drive system, triplex ceramic plunger design and a nickel-plated brass manifold, the Centurion P8 is the epitome of performance engineering.

1. ADJUSTABLE PRESSURE EXTERNAL UNLOADER
2. OIL FILL PORT
3. QUICK CONNECT HIGH PRESSURE HOSE OUTLET
4. THERMAL RELIEF VALVE
5. 3/4" INLET FOR GARDEN HOSE
6. BRASS MANIFOLD
7. BELT DRIVE SOLID SHAFT



PMR / PUMPS
MADE READY

MAX PSI
3,500



5.5 GPM
FLOW



24 MM
KEYED SHAFT



BELT DRIVE
SOLID SHAFT
GAS / ELECTRIC



TECH SPECS

PUMP STYLE: Triplex

RPM: 1,450

SOAP INJECTOR: Adjustable

MAX PSI: 3,500

MAX INLET TEMPERATURE: 60°C / 140°F

MANIFOLD TYPE: Nickel-Plated Brass

MAX GPM: 5.5

PMR PART #: 85.129.190B

THERMAL RELIEF VALVE: 85.300.024

UNLOADER TYPE: External

PUMP MODEL: CTB4S

OIL CAPACITY: 32 fl oz

INLET SIZE: 3/4" Garden Hose Fitting (GHF)

DRIVE TYPE: Belt drive (Gas / Electric)

OIL TYPE: 30W non-detergent

DISCHARGE SIZE: 3/8" Brass Quick Connect

SHAFT SIZE: 24mm

WEIGHT: 27.5 lbs

PLUNGER (PISTON): Ceramic

WARRANTY: 7 Years



PMR configuration available with unloader, discharge, 3/8" QC outlet, 3/4" garden hose inlet, thermal relief valve, and adjustable soap injector (not all fittings pictured).
Bare pumps do not include the above fittings.

SCAN HERE
TO LEARN
MORE ABOUT
THIS PUMP



www.CENTURIONPUMP.COM

UPC 777987405516