POWER EQUIPMENT

3,000 PSI - 4.0 GPM HOT WATER PRESSURE WASHER WITH 7.5HP MOTOR AND GENERAL TRIPLEX PUMP



MODEL: X-HW3075EW3GEN

FEATURES

- 7.5 HP, three phase premium efficiency, inverterduty motor delivers efficiency and reliability suited for commercial applications.
- Belt drive system provides longest pump life possible by lowering its heat, vibration and RPM.
- Commercial grade General triplex pump featuring reinforced body, forged brass manifold, solid ceramic plungers, stainless steel check valves and thermal release valve.
- Auto start/stop system with 8 second time delay. Pump activates only the trigger of the spray wand is squeezed.
- External unloader provides superior cooling and versatility to further enhance pump life.
- Fully insulated, electric powered heater tank. Fully automatic with low water safety shutdown.
- The heater can be turned off and controlled with the adjustable thermostat that can be set up to 82°/180°F.
- Industrial grade accessories included are a 50 foot highpressure hose, spray gun wand assembly, and five spray nozzles.





Scan the QR code with your mobile device and discover more about this BE Pressure washer.

MOTOR

MODEL: INVERTER DUTY

 HORSE POWER:
 7.5

 AMPS:
 80

 VOLTS:
 575

 PHASE:
 THREE

AUTO START/STOP: 8 SECOND DELAY

PUMP SPECS

MODEL: GENERAL TYPE: TRIPLEX

OIL TYPE: **30W NON-DETERGENT** SOAP SYSTEM: **ADJUSTABLE INJECTOR**

UNLOADER

TYPE: EXTERNAL W/36" HOSE

HEAT EXCHANGER

THERMOSTAT: ON/OFF AND ADJUSTABLE

MAX TEMP: 82°C / 180°F

HEATING: **HEATED WATER TANK**

POWER SOURCE: **ELECTRIC**

ACCESSORIES

HOSE TYPE: 50' X 3/8" WIRE BRAIDED

PART NUMBER: **85.238.251**

NOZZLES: 0°, 15°, 40° AND SOAPER

PART NUMBER: 85.210.035BEP
GUN WAND: 36" INSULATED
PART NUMBER: 85.205.604
FITTINGS: QUICK CONNECT

FRAME

MATERIAL: POWDER COATED

SHIPPING SIZE

LxWxH: **43" x 20" x 42"**WEIGHT: **695 LBS**

UNIT SIZE

LxWxH: **42" x 20" x 41"**WEIGHT: **630 LBS**

WARRANTY

MOTOR: 2 YEARS
PUMP: 5 YEARS
HEATER: 3 YEARS
UPC: 777897324921

05-2021