## 3,500 PSI - 5.2 GPM HOT WATER PRESSURE WASHER WITH HONDA GX690 ENGINE AND GENERAL PUMP



MODEL: Z5535GPBDH

## **FEATURES**

- Industrial Honda GX690 Engine delivers energy efficiency and reliability & dependability, suited for industrial use.
- Belt drive system provides long pump life by lowering RPM, heat transfer & vibration.
- Industrial Grade General Pump featuring reinforced body, forged brass manifold, solid ceramic plungers, thermal release valve and improved heat dissipation.
- The burner Beckett Burners with adjustable thermostat Diagnostic LED Lights.
- External unloader effectively regulates water flow in a compact design.
- Accessories includes Trigger Gun Control with 4' Lance, Quick Connect Nozzles, 50' high-pressure hose.



**ENGINE** 

MODEL: HONDA GX690

DISPLACEMENT: 688CC

FUEL TYPE: 86 OCTANE, UP TO 10% ETHANOL

OIL TYPE: SAE 10W30

**PUMP SPECS** 

MODEL: GENERAL TS2021

TYPE: TRIPLEX

OIL TYPE: 30W NON-DETERGENT

**BURNER** 

MAX HEAT: 93°C/200°F

HEATING COIL: 1/2" COLD ROLLED STEEL
COIL TUBE LENGTH: 63' LENGTH OF TUBING

FUEL TYPE: **DIESEL** 

**ACCESSORIES** 

HOSE TYPE: 50' X 3/8" WIRE BRAIDED

NOZZLES: 15°, 25°, 40°, SOAPER

GUN WAND: 48" INSULATED

FITTINGS: QUICK CONNECT

FRAME

MATERIAL: POWDER COATED

**UNIT SIZE** 

LxWxH: **42" x 36.5" x 54"**WEIGHT: **750 LBS** 

**WARRANTY** 

MOTOR: 3 YEARS PUMP: 5 YEARS HEATING COIL: 3 YEARS

## 3,500 PSI - 5.2 GPM HOT WATER PRESSURE WASHER WITH HONDA GX690 ENGINE AND GENERAL PUMP



MODEL: **Z5535GPBDH** 

## **FEATURES**

- Industrial Honda GX690 Engine delivers energy efficiency and reliability & dependability, suited for industrial use.
- **Belt drive** system provides long pump life by lowering RPM, heat transfer & vibration.
- Industrial Grade General Pump featuring reinforced body, forged brass manifold, solid ceramic plungers, thermal release valve and improved heat dissipation.
- The burner Beckett Burners with adjustable thermostat Diagnostic LED Lights.
- External unloader effectively regulates water flow in a compact design.
- Accessories includes Trigger Gun C Lance, Quick Connect Nozzles, 50' hose.



**ENGINE** 

MODEL: HONDA GX690

DISPLACEMENT: **688CC** 

FUEL TYPE: 86 OCTANE, UP TO 10% ETHANOL

OIL TYPE: SAE 10W30

**PUMP SPECS** 

MODEL: GENERAL TS2021

TYPE: TRIPLEX

OIL TYPE: 30W NON-DETERGENT

**BURNER** 

MAX HEAT: 93°C / 200°F

HEATING COIL: 1/2" COLD ROLLED STEEL
COIL TUBE LENGTH: 63' LENGTH OF TUBING

FUEL TYPE: **DIESEL** 

**ACCESSORIES** 

HOSE TYPE: 50' X 3/8" WIRE BRAIDED

NOZZLES: 15°, 25°, 40°, SOAPER

GUN WAND: 48" INSULATED

FITTINGS: QUICK CONNECT

FRAME

MATERIAL: POWDER COATED

**UNIT SIZE** 

LxWxH: **42"** x **36.5"** x **54"** 

WEIGHT: 750 LBS

**WARRANTY** 

MOTOR: 3 YEARS
PUMP: 5 YEARS
HEATING COIL: 3 YEARS